

To Debug our DLT issue we uncomment the bottom-most lines.

```
MINGW64:/c/Users/Candace/Projects/tssgTech/tools/docker/scheduledb/dbapp/src/app/meeting-add
Comment is required
  </span>
</div>

  <div class="form-group">
    <!-- <button type='submit' class='btn btn-primary' [disabled]='meetingFo
rm.invalid'>Add</button> -->
    <button type='submit' class='btn btn-primary'>Add</button>
    &nbsp;
    <button type="reset" class="btn btn-success" (click)="cancel()">Cancel</
button>
  </div>
</div>
</div>
</form>
<div *ngIf="errorMsg" class="alert alert-danger">{{errorMsg}}</div>
<div><br/><br/><br/><br/><a id="bottom"></a></div>
<!--
<br /><br />
Angular Generated Form Model : {{meetingForm.value | json}}
<br /><br />
Our Meeting Model : {{meeting | json}}
-->
</rc/app/meeting-add/meeting-add.component.html [unix] (04:41 06/12/2019)75,2 Bot
```

Like this.

```
MINGW64:/c:/Users/Candace/Projects/tssgTech/tools/docker/scheduledb/dbapp/src/app/meeting-add
Comment is required
  </span>
</div>

  <div class="form-group">
    <!-- <button type='submit' class='btn btn-primary' [disabled]='meetingFo
rm.invalid'>Add</button> -->
    <button type='submit' class='btn btn-primary'>Add</button>
      &nbsp;
    <button type="reset" class="btn btn-success" (click)="cancel()">Cancel</
button>
  </div>
</div>
</div>
</div>
</form>
<div *ngIf="errorMsg" class="alert alert-danger">{{errorMsg}}</div>
<div><br/><br/><br/><br/><a id="bottom"></a></div>
<br /><br />
Angular Generated Form Model : {{meetingForm.value | json}}
<br /><br />
Our Meeting Model : {{meeting | json}}
~
~
<rc/app/meeting-add/meeting-add.component.html [unix] (19:07 09/12/2019)78,1 Bot
"meeting-add.component.html" [unix] 78L, 3950C written
```

This allows us to view variables within the Angular Form.

The screenshot shows a web browser window with two tabs, both titled "TssgDbApp". The address bar shows the URL "192.168.99.100:4200/meeting/create". The browser's developer tools are open, showing the console with a log of messages. The main content area displays a form titled "Add New Meeting".

The form fields are:

- Meeting Id (must be unique):
- Team Name (select one):
- Venue Name (select one):
- Meeting Date:
- Start Time:
- End Time:
- Comments:

At the bottom of the form, there are "Add" and "Cancel" buttons. Below the form, the Angular Generated Form Model is displayed:

```
Angular Generated Form Model : { "_id": "7987", "team": "DevOps", "venue": "Action", "meetingDate": "2019-12-15T03:43:09.000Z", "comments": "this is a test" }
```

Below the model, the form's data is shown:

```
Our Meeting Model : { "_id": "7987", "team": "DevOps", "venue": "Action", "meetingDate": "2019-12-15T03:43:09.000Z", "startTime": "2019-12-09T18:00:00.056Z", "endTime": "2019-12-09T20:00:00.144Z", "comments": "this is a test" }
```

The developer console shows a log of messages, including a warning about a group serial and a message about the application being in development mode.

A small black box with the text "Jim T" is visible in the bottom right corner of the browser window.